



## JONI MULTI 100L



The Joni jacketed kettle Multi model 100L is a convenient and simple to use classic non-mixing kettle with an electric tilt function.

Incredible time and labour saver in process and production cooking for optimal temperature control, safety and efficiency.

Joni kettles are unique in their seamless construction. One piece welded high grade stainless steel with no manufacturing joins inside the bowl. This maximises efficiency, hygiene, ease of cleaning and overall life expectancy. Supplied as standard with AutoTemp 32 control

### Winning Features

- Electric tilt function
- Electric water flow meter
- Quick and easy to use and empty
- Unheated, insulated top
- Min 400mm tilt height
- Easy to clean
- Seamless construction
- Several kettles can be linked together
- Infinitely variable heating

Auto-filling steam generator

Link the Multi with MultiMix, Opti and OptiMix for kitchens seeking labour saving and user-friendly solutions.

Kettles are supplied as standard with a lightweight tight-closing lid for added safety and efficiency. Ergonomic, quick and easy to empty and maintain. The Multi Joni jacketed kettles are available in multiple litre capacities from 40L through to 300L and can be supplied as a steam or electric heated kettle.

Multi 100L Standard AutoTemp 32 control features

Electric tilt with TiltBack function

Digital control and display of inner kettle temperature

Electronic control of jacket temperature

Clock and timer

Cold water tap for filling

Digital controls with infinitely variable temperature

Pressure or overheating indicator light

Automatic steam water level control

Multi kettles can be fitted with optional additional functions and a range of accessories.

(Multi100L)

SKU

Multi100L

Type

Joni Multi

Category

Kettle

Type

Multi

Construction

Stainless steel

Working pressure

1.0 bar

Max. steam temperature

120° C

Max, temperature on outside of kettle bowl

Less 40° C

Working height

900 mm

Max. cooking capacity

100 litres

Stirrer speed rpm min-max

NA

Weight (kg)

201

Dimensions W x D x H (mm)

1335 x 1063 x 1819

Power connection

3 Phase, 400V, 50Hz,

Rated power (kw)

20.00

Current consumption (A)

3 x 29

Time to boil water 10°-90° C (min)

app. 28

Water connection

½", 1.5-6 bar, 35L/min

AutoTemp 02e Control

Standard

AutoTemp 11 Control  
Option

AutoTemp 31 Control  
NA

Butterfly valve  
Option

Sieve plate  
Option

Spray gun  
Option

MultiClean  
NA

Chilling  
Option

Shipping Weight  
251.0000kg

Shipping Width  
1.635m

Shipping Height  
1.500m

Shipping Length  
1.250m

Shipping Cubic  
3.065625000m<sup>3</sup>